



Dimensions and Geometry of Vivente Bikes

	Frame Size								
	Extra Small (DTT)	Small	Small (DTT)	Medium	Medium (DTT)	Large	X Large	XX Large	XXX Large
Rear tyre size as supplied	26 x 1.4" radius 317mm	700 x 35C radius 347mm	700 x 35C radius 347mm	700 x 35C	700 x 35C	700 x 35C	700 x 35C	700 x 35C	700 x 35C
Front tyre size as supplied	26 x 1.4"	700 x 32C	700 x 32C	700 x 32C	700 x 32C	700 x 32C	700 x 32C	700 x 32C	700 x 32C
Max front & rear tyre clearance	26 x 2.0"	700 x 50C	700 x 50C	700 x 50C	700 x 50C	700 x 50C	700 x 50C	700 x 50C	700 x 50C
Seat tube C to Top (mm & ")	384 (15-1/8")	430 (17")	430 (17")	490 (19-1/4")	490 (19-1/4")	540 (21-1/4")	590 (23-1/4")	630 (24-3/4")	670 (26-3/8")
Seat tube C to upper edge of TT (mm & ")	222 (8-3/4")	390 (15-3/8")	268 (10-9/16")	459 (18")	328 (12-15/16")	508 (20")	558 (22")	597 (23-1/2")	636 (25")
Top tube (effective) (mm & ")	498 (19-5/8")	541 (21-1/4")	541 (21-1/4")	566 (22-1/4")	566 (22-1/4")	575 (22-5/8")	590 (23-1/4")	620 (24-3/8")	640 (25-1/4")
Head tube (mm & ")	100 (4")	100 (4")	100 (4")	145 (5")	145 (5")	165 (6-1/2")	180 (7")	180 (7")	200 (7-7/8")
Standover height at middle of TT	597 (23-1/2")	717 (28-1/4")	647 (25-1/2")	774 (30-1/2")	698 (27-1/2")	808 (31-3/4")	844 (33")	859 (34")	887 (35")
Normal rider height range bare feet (cm & ")	149-157 (4'11"-5'2")	158-166 (5'2"-5'5")	158-166 (5'2"-5'5")	167-175 (5'6"-5'9")	167-175 (5'6"-5'9")	176-184 (5'9"-6')	185-193 (6'1"-6'4")	194-201 (6'4"-6'7")	202-210 (6'8"-6'11")
Bottom Bracket drop* (mm & ")	50 (2")	75 (3")	75 (3")	75 (3")	75 (3")	75 (3")	75 (3")	75 (3")	75 (3")
Wheel base (mm & ")	996 (39-1/5")	1064 (41-7/8")	1064 (41-7/8")	1089 (42-7/8")	1089 (42-7/8")	1092 (43")	1101 (43-3/8")	1128 (44-5/16")	1141 (45")
Chain stays C to C (mm & ")	436 (17-3/16")	463 (18-1/4")	463 (18-1/4")	463 (18-1/4")	463 (18-1/4")	463 (18-1/4")	463 (18-1/4")	463 (18-1/4")	460 (18-1/8")
Head angle (degrees)	71	71	71	71	71	71	71	71	71
Seat angle (degrees)	74.5	74.5	74.5	74	74	73.5	73	72.5	72.5
Fork length axle centre to under crown race (mm & ")	388 (15-1/4") (fork diag is 376 & frame is 388)	403 (15-7/8")	403 (15-7/8")	403 (15-7/8")	403 (15-7/8")	403 (15-7/8")	403 (15-7/8")	403 (15-7/8")	403 (15-7/8")
Fork trail with 35C tyres	62mm	64mm	64mm	64mm	64mm	64mm	64mm	64mm	64mm
Fork rake	45mm	52mm	52mm	52mm	52mm	52mm	52mm	52mm	52mm
Reach*	605 (23-3/4")	655 (25-3/4")	655 (25-3/4")	710 (28")	710 (28")	730 (28-3/4")	780 (30-3/4")	820 (32-1/4")	840 (33")
Crank length (mm)	165	165	165	170	170	170	175	175	175
Stem length (mm)	60	80	80	100	100	120	120	130	130
Handlebar width Trekking bars (mm) (bore= 25.4)	580	580	580	580	580	580	580	580	580
Handlebar width drop bars (bore= 26.0)	400	400	400	420	420	440	460	460	460
Handlebar width riser bars (mm) (bore= 31.8)	580	580	580	600	600	600	640	640	640

*C-C means centre to centre

*TT means top tube

*DT means down tube

*DTT means Dropped Top Tube (Once called a "ladies" frame)

*ST means seat tube

*BB means bottom bracket

* Reach means the sitbone position on seat to the centre of

*BB Drop is the vertical difference between the wheel axle height and the bottom bracket shell.